






Specification Matrix















20-50mm



20-50mm



20-50mm




20-50mm

Ivalialex	
Buff 1	

Buff 2

Blue

20-50mm



20-50mm

Green

20-50mm

Red

20-50mm

Salmon Terracotta

erracotta Grey

Brown

NatraTex Cotswold	Buff	Buff 2 (Classic)		
Dense Grade Available	⊘	⊘		
Heavy Duty Available	⊘	lacksquare		
Fibre Enhanced Available	•			
*Porous for SuDS	•	•		
Available in Eco range	•	•		
Nominal aggregate size	6mm or 10mm	6mm or 10mm		
Nominal aggregate type	Crushed Rock	Crushed Rock		
Curing time to use	up to 24 hrs	up to 24 hrs		
Polymer Modified Binder	•	•		
Total thickness (see product data sheet)	20-50mm	20-50mm		

	2000年1000年1000年		Section 4 to the section		《李明教大师》		SECOND PROPERTY.
Blue	Gold	Green	Red	Salmon	Terracotta	Grey	Brown
⊘	②	②	②	②	②	②	⊘
✓	⊘	\bigcirc	⊘	⊘	⊘	⊘	⊘
⊘	•	⊘	⊘	•	⊘	•	⊘
-	•	⊘	⊘	•	•	•	•
-			Ø				
6mm or 10mm	6mm or 10mm	6mm or 10mm	6mm or 10mm	6mm or 10mm	6mm or 10mm	6mm or 10mm	6mm or 10mm
Crushed Rock	Crushed Rock	Crushed Rock	Crushed Rock	Crushed Rock	Crushed Rock	Crushed Rock	Crushed Rock
up to 24 hrs	up to 24 hrs	up to 24 hrs	up to 24 hrs	up to 24 hrs	up to 24 hrs	up to 24 hrs	up to 24 hrs
•	•	•	•	•		•	

^{*}Subject to product review